



US006231444B1

(12) **United States Patent**  
**Goto et al.**

(10) **Patent No.:** **US 6,231,444 B1**  
(45) **Date of Patent:** **May 15, 2001**

(54) **OPERATING DEVICE FOR GAME MACHINE**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Teiyu Goto**, Saitama; **Hiroki Ogata**, Chiba, both of (JP)

6-85821 11/1994 (JP) .  
7-24147 1/1995 (JP) .  
8-24439 1/1996 (JP) .  
8-45392 2/1996 (JP) .  
9-167050 6/1997 (JP) .

(73) Assignee: **Sony Computer Entertainment Inc.** (JP)

\* cited by examiner

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

*Primary Examiner*—Valencia Martin-Wallace  
*Assistant Examiner*—Julie Kasick  
(74) *Attorney, Agent, or Firm*—Lerner, David, Littenberg, Krumholz & Mentlik, LLP

(21) Appl. No.: **09/091,121**

(22) PCT Filed: **Apr. 11, 1997**

(86) PCT No.: **PCT/JP97/01274**

§ 371 Date: **Sep. 24, 1998**

§ 102(e) Date: **Sep. 24, 1998**

(87) PCT Pub. No.: **WO98/16285**

PCT Pub. Date: **Apr. 23, 1998**

(30) **Foreign Application Priority Data**

Oct. 11, 1996 (JP) ..... 8-30240

(51) **Int. Cl.<sup>7</sup>** ..... **A63F 13/02**

(52) **U.S. Cl.** ..... **463/37; 273/148 B**

(58) **Field of Search** ..... **463/37, 38; 273/148 B**

(56) **References Cited**


U.S. PATENT DOCUMENTS

5,716,274 \* 2/1998 Goto et al. .... 463/37  
5,759,100 \* 6/1998 Nakanishi ..... 463/37  
5,820,462 \* 10/1998 Yokoi et al. .... 463/37  
5,897,437 \* 4/1999 Nishiumi et al. .... 463/47  
6,001,014 \* 12/1999 Ogata et al. .... 463/37  
6,001,015 \* 12/1999 Nishiumi et al. .... 463/38

(57) **ABSTRACT**

An operating device used in a game machine for playing a television game includes a main body portion of the operating device and first and second grip portions protruding from one side on respective end parts of the main body portion. A first operating unit is mounted on one end of the main body portion and a second operating unit is mounted on the opposite end of the main body portion. The first and second operating units are provided with a plurality of thrusting operators protruding from the upper surface of the main body portion and a plurality of signal input elements actuated by the thrusting operators. A third operating unit and a fourth operating unit are arranged facing each other on the proximal ends of the first and second grip portions. Each of the third and fourth operating units has a rotation member and a plurality of signal input devices actuated by the rotation member. When the first and second grip portions are gripped, the third and fourth operating units can be manipulated by a thumb finger of a hand gripping the first or second grip portion. The operating device further includes vibration imparting mechanism for imparting vibrations to the user's hands.

**20 Claims, 14 Drawing Sheets**






FIG. 1




FIG. 2




FIG.3




FIG.4




FIG. 5




FIG. 6






FIG. 8




FIG. 9






FIG.11





FIG.12



**FIG.13**




FIG.14




FIG. 15







FIG. 16



**FIG.17**



**FIG.18**



**FIG.19**






FIG. 21

## OPERATING DEVICE FOR GAME MACHINE

### TECHNICAL FIELD

This invention relates to an operating device used in a game machine employing a display device for, for example, a television receiver. More particularly, it relates to an operating device controlling the operation of rotating a display character displayed on a display screen, continuously changing its speed of movement or deforming the display character.

### BACKGROUND ART

Heretofore, a game machine employing a television receiver has a main body portion connected to the television receiver used as a display device, and an operating device connected to this main body portion of the game machine over a connection cable for controlling the display character displayed on the display screen of the television receiver.

The main body portion of the game machine has enclosed therein a disc driving unit for reproducing an optical disc as a recording medium carrying a recorded game program and a picture processing device for displaying the display character along with a background scene on the screen of the television receiver in accordance with the game program recorded on the optical disc.

Plural operating buttons are arranged in the operating device connected to the main body portion of the game machine. The user operates these operating buttons provided on the operating device for entering to the picture processing device the command information concerning the movement of the display character displayed on the display screen of the television receiver for controlling the direction of movement of the display character in accordance with the command information for carrying out the game.

The operating device used in this sort of the game machine is used by being gripped with hand or finger. That is, such operating device is used which has, on its one side, a direction command operating unit including a cross-shaped or circular direction command operating button and which also has, on its other side, a function setting unit including plural function setting/executing buttons for setting or executing the operating functions of the display characters. The direction command operator includes four switches arranged at right angles to one another and having operating units adapted for being contacted with or moved away from associated contacts. These switches are selectively turned on and off by the cross-shaped or circular direction command operating buttons for moving the display characters. For example, the display character is moved in a direction along which is arrayed the one of the four switches that has been turned on. The function setting/executing unit has switches arranged in association with the plural function setting/executing buttons. By turning on the switch associated with the function setting/executing button, the function of the display character allocated to the button is set or the function proper to the display character is executed.

Since the direction command operating unit of the operating device simply affords a command signal for moving the display character in a direction along which is arrayed the one of the four switches arranged at right angle to each other, the operating unit cannot issue the command information of rotating the display character as it is advanced, or of changing the line of sight of the display character. The result is that difficulties are encountered in constructing the game program employing a display character performing variegated movements.

On the other hand, since the switches making up the direction command operating unit merely issue the command information of controlling the movement of the display character by being turned on and off by actuation of the direction command operating buttons, the display character performs intermittent movements, while being unable to perform a series of continuous movements.

Thus, such an operating device has been proposed having an operating unit to which can be entered a command signal enabling the display character to be moved as it rotates or as it changes its speed or enabling the display character to change its form or configuration.

An operating device of this type has been disclosed in Japanese Laid-Open Patent Application 7-88252.

However, if a large number of operating units are provided in the operating device, it becomes difficult to smoothly select the operating units.

### SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide an operating device for a game machine capable of smoothly operating a large number of operating units.

It is another object of the present invention to provide an operating device for a game machine designed for facilitating the operation of the operating unit issuing the command information for moving the display character as it rotates or as it changes its speed or enabling the display character to change its form or configuration.

It is still another object of the present invention to provide an operating device for a game machine enabling the use of a game program having a display character capable of executing variegated movements or operations.

It is yet another object of the present invention to provide an operating device for a game machine enabling execution of a game having excellent simulated reality feeling.

An operating device used in a game machine for playing a television game includes a main body portion of the operating device and first and second grip portions protruded from one side on respective end parts of the main body portion. A first operating unit is mounted on one end of the main body portion and a second operating unit is mounted on the opposite end of the main body portion. The first and second operating units are provided with a plurality of thrusting operators protruded from the upper surface of the main body portion and a plurality of signal input elements actuated by the thrusting operators. A third operating unit and a fourth operating unit are arranged facing each other on the proximal ends of the first and second grip portions. Each of the third and fourth operating units has a rotation member and a plurality of signal input devices actuated by the rotation member. When the first and second grip portions are gripped, the third and fourth operating units can be manipulated by a thumb finger of a hand gripping the first or second gripping portion.

The third and fourth operating units, provided with signal input elements manipulated by the rotation member, can execute movements of a display character on a screen, such as simultaneously rotating and moving the display character, moving it with variable speed or changing its configuration, while entering a command signal to the main body portion of the game machine.

Since the first and second grip portions, protruded from the end portions of the main body portion, are spaced apart from each other towards the distal ends thereof while being formed for extending downwardly of the main body portion,

the index finger can be extended over the operators of the first and second operating units protruded over the upper surface of the main body portion when the user is gripping the first or second gripping portion.

In the lower surface of the main body portion is formed an engagement recess engaged by a portion of the hand or finger when the first and/or second gripping portion is gripped by the hand or finger. With the engagement recess engaged by the hand or finger, the operating device can be gripped reliably in stable states.

Moreover, a finger support is provided in register with the engagement recess formed on the front side of the main body portion.

On the respective ends on the front surface of the main body portion are mounted fifth and sixth operating portions.

A vibration imparting mechanism is enclosed within the operating device of the present invention for imparting vibrations to the user during operation for executing the game with excellent simulated reality feeling. The vibration imparting mechanism is arranged in at least one of the grip portions and includes a driving motor and an offset member mounted on a driving shaft of the driving motor.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing an operating device for a game machine according to the present invention.

FIG. 2 is a plan view of the operating device for a game machine shown in FIG. 1.

FIG. 3 is a back side view of the operating device for the game machine shown in FIG. 1.

FIG. 4 is a front view of the operating device for the game machine shown in FIG. 1.

FIG. 5 is a right-hand side view of the operating device for the game machine shown in FIG. 1.

FIG. 6 is a left-hand side view of the operating device for the game machine shown in FIG. 1.

FIG. 7 is a perspective view showing the state of use of the operating device for the game machine shown in FIG. 1.

FIG. 8 is a side view showing the state of use of the operating device for the game machine shown in FIG. 1, with the operating device being mounted on a mounting surface.

FIG. 9 is a perspective view showing essential portions of the first operating unit.

FIG. 10 is a partial cross-sectional view showing the first operating unit.

FIG. 11 is a cross-sectional view showing the inoperative state of first to fourth thrusting operators making up the first operating unit.

FIG. 12 is a cross-sectional view showing the state of the second thrusting operator of the first operating unit being thrust.

FIG. 13 is a cross-sectional view showing the state of the second thrusting operator of the first operating unit having been thrust.

FIG. 14 is an exploded perspective view showing a multi-directional input device making up third and fourth operating units.

FIG. 15 is a cross-sectional view showing the multi-directional input device with an operating shaft in its initial state.

FIG. 16 is a cross-sectional view showing the multi-directional input device with the operating shaft having been rotated.

FIG. 17 is a cross-sectional view showing the multi-directional input device showing the state of operating a thrusting type switch element.

FIG. 18 is a cross-sectional view showing the multi-directional input device showing the state of the thrusting type switch element having been operated.

FIG. 19 is an exploded perspective view showing a vibration imparting mechanism.

FIG. 20 is a perspective view showing the state in which the vibrating imparting mechanism has been built in the main body portion of the game machine.

FIG. 21 is a plan view showing the state in which the operating device for the game machine according to the present invention has been connected to the main body portion of the game machine.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to the drawings, an operating device for a game machine according to the present invention will be explained in detail.

The operating device for the game machine is connected to a main body portion of the game machine for controlling the operation of the present game machine for executing the game software recorded on an optical disc. The main body portion of the game machine has enclosed therein a disc driving unit for reproducing an optical disc as a recording medium having a game program recorded thereon and a picture processing unit for displaying a display character along with a background picture on the screen of a television receiver in accordance with a game program recorded on the optical disc.

The operating device 1 for the game machine according to the present invention includes a main body portion 4 made up of an upper half 2 and a lower half 3 abutted and secured to each other such as with set-screws, as shown in FIG. 1. Referring to FIGS. 1 and 2, a first grip portion 5 and a second grip portion 6 are protuberantly formed on the lateral surface on both ends of the main body portion 4 so that, when the device 1 is connected to the main body portion of the game machine for playing the game, the grip portions 5, 6 will be gripped by being held in their entirety with the user's palms. These first and second grip portions are progressively spaced apart from each other towards their distal ends while being directed downwardly of the main body portion 4, as shown in FIGS. 2, 3 and 4. For enabling the gripping over an extended time, the first and second grip portions 5, 6 are tapered from their connection to the main body portion 4, while being arcuately shaped on the peripheral surfaces and on the distal ends thereof, as shown in FIGS. 2, 5 and 6.

On one end side of the main body portion 4 is mounted a first operating unit 9 having first to fourth thrusting operators 8a, 8b, 8c and 8d protruding from the upper surface of the main body portion 4 at right angles to each other, as shown in FIGS. 1 and 2. The first to fourth thrusting operators 8a, 8b, 8c and 8d making up the first operating unit 9 are unified to a rotation actuating member 10 having its center portion supported for rotation and are arrayed at right angles to one another about the center of rotation of the rotation actuating member 10. That is, the first to fourth thrusting operators 8a, 8b, 8c and 8d making up the first operating unit 9 are connected as one to one another. The first operator 9 is provided with switch devices, as signal input devices, in association with the first to fourth thrusting operators 8a, 8b, 8c and 8d. The first operator 9 operates as a direction command controller controlling the movement of the display

character, such that, by selectively actuating the first to fourth thrusting operators **8a**, **8b**, **8c** and **8d** and by selectively turning on/off the switch devices associated with the thrusting operators, the display character is moved in the arraying direction of the thrust operators **8a**, **8b**, **8c** or **8d**.

On the opposite side of the main body portion **4** is mounted a second operating unit **12** having protuberant first to fourth thrusting operators **11a**, **11b**, **11c** and **11d** arrayed at right angles to one another. These first to fourth thrusting operators **11a**, **11b**, **11c** and **11d** are formed as independent members and switch devices as signal input devices are mounted in association with these thrusting operators **11a**, **11b**, **11c** and **11d**. By turning on the switch devices associated with the first to fourth thrusting operators **11a**, **11b**, **11c** and **11d**, the second operating unit **12** sets the functions of the display character allocated to the thrusting operators **11a**, **11b**, **11c** and **11d** or executes the functions of the display character, the second operating unit **12** thus operating as a function setting and/or executing section.

The operating device **1** of the present invention has third and fourth operating units **14**, **15** on the proximal sides of the first and second grip portions **5**, **6** where they connect to main body portion **4**. Each of these third and fourth operating devices **14**, **15** includes a rotation member **16** rotatable in a 360° direction about a pivot **16a** as the center of rotation and a signal input element, such as a variable resistance element, operated by this rotation member **16**. Specifically, the rotation member **16** is mounted towards the distal end of a pivot **16a** mounted so as to be reset to its neutral position by a biasing member and is rotated in a 360° direction about the pivot **16a** as center of rotation. These third and fourth operating units **14**, **15** are used for enabling inputting of a command signal for enabling analog movements such as combined rotation and linear movement, linear movement with a variable speed or change of the configuration of the display character by rotational operation of the rotation member **16**.

On the left and right ends towards the front side of the main body portion **4** opposite to its back side from which are protruded the first and second grip portions **5**, **6** are arranged fifth and sixth operating units **17**, **18**. These fifth and sixth operating units **17**, **18** include first and second thrusting operators **19a**, **19b** and **20a**, **20b**, respectively. These thrusting operators **19a**, **19b** and **20a**, **20b** are associated with switch devices. By turning on the switch associated with the first and second thrusting operators **19a**, **19b** and **20a**, **20b**, the fifth and sixth operating units **17**, **18** set the function of the display character allocated to the thrusting operators **19a**, **19b** and **20a**, **20b** or execute the functions owned by the display character, the fifth and sixth operating units **17**, **18** thus operating as function setting and/or executing sections.

Between the first operating unit **9** and the second operating unit **12** on the upper surface of the main body portion **4** are mounted, side-by-side, a start switch **22** for commanding start of a game and a selection switch **23** for selecting, at the time of starting the game, the degree of ease or difficulty with which the game is played. Between the third and fourth operating units **14**, **15** on the upper surface of the main body portion **4** are mounted a mode select on switch **24** for selecting the operating mode of the third and fourth operating units **14**, **15** and a display unit **25** for displaying the state of the operating mode of the third and fourth operating units **14**, **15**. This display unit **25** is constituted by a light emitting device, such as light emitting diode. By switching the mode select on switch **24**, an operating mode enabling the inputting of a command signal from the third and fourth operating units **14**, **15** or an operating mode

inhibiting the inputting of the command signal from the third and fourth operating units **14**, **15** is selected. In addition, an operating mode is selected which enables inputting of a command signal from the third and fourth operating units **14**, **15** and which has switched the functions of the first to fourth thrusting operators **11a** to **11d** and the functions of the first and second thrusting operators **19a**, **19b**, **20a**, **20b** of the fifth and sixth operating units **17**, **18**. Depending on the states of the operating modes, the display unit **25** is turned on and off, with switching of the display light.

In the lower surface of the main body portion **4** are formed engagement recesses **26**, **27** engaged by a portion of left and right fingers Lf, Rf when the first and/or second grip portions **5**, **6** are gripped by these fingers, as shown in FIG. 7. These engagement recesses **26**, **27** are formed as smoothly curved reentrant portions, as shown in FIGS. 5 and 6.

In register with the engagement recesses **26**, **27** on the front side of the main body portion **4** are formed depending finger supports **28**, **29**, as also shown in FIGS. 5 and 6. Specifically, the finger supports **28**, **29** are protruded from the lower ends of protuberant portions **31**, **32** on both ends on the front side of the main body portion **4** carrying the fifth and sixth operating units **17**, **18**.

With the above-described operating device of the present invention, in which the first and second grip portions **5**, **6** are protuberantly formed on the main body portion **4**, since the first and second grip portions **5**, **6** are held by being entirely wrapped with both palms, there is no necessity of supporting the main body portion **4** with fingers, such that the operating device can be gripped in such a state that ten fingers at the maximum and six fingers in the least of both hands can be moved freely. If, for example, the first and second grip portions **5**, **6** are gripped as they are wrapped entirely with both palms, both thumb fingers Lf1, Rf1 of left and right hands can be extended over rotation members **16** of the third and fourth operating units **14**, **15**, and other the first to fourth thrusting operators **8a** to **8d** of the first operating unit **9** and the first to fourth thrusting operators **11a** to **11d** of the second operating unit **12** to enable selective thrusting of rotation member **16**, thrusting operators **8a** to **8d** and the thrusting operators **11a** to **11d**. In particular, since the rotation members **16** of the third and fourth operating units **14**, **15** are arranged facing the proximal ends which are coupling sides to the main body portion **4** of the first and second grip portions **5**, **6** gripped by being entirely enclosed by both palms, the rotation members **16** lie closest to the thumb fingers Rf1, Lf1 when the first and second grip portions **5**, **6** are gripped by left and right hands. Thus, the rotation members **16** can be turned easily with the thumb fingers Rf1, Lf1.

Also, when the first and second grip portions **5**, **6** are gripped by being entirely enclosed by both palms, as shown in FIG. 7, the index fingers Rf2, Lf2 and second fingers Rf3, Lf3 of both hands can be extended to positions enabling selective thrusting of the first and second thrusting operators **19a**, **19b** and **20a**, **20b** of the fifth and sixth operating units **17**, **18**.

Thus, when the operating device **1** is gripped by both hands, the first and second grip portions **5**, **6** are enclosed with both palms and both third fingers Lf4, Rf4 and/or little fingers Lf5, Rf5 of left and right hands can be engaged in the engagement recesses **26**, **27** and set on the finger supports **28**, **29**, so that the main body portion **4** can be gripped in position. Since the fingers can be set in position on the first to sixth grip portions **9**, **12**, **14**, **15**, **17** and **18**, correct operations can be realized.

Instead of being gripped by hand and fingers, the operating device 1 can also be set on a planar setting surface S, such as a table, as shown in FIG. 8. The operating device 1 is designed so that, if the device 1 is set on the setting surface S with the distal ends of the first and second grip portions 5, 6 and the distal ends of the finger supports 28, 29 as supports, the operating surfaces of the first to fourth thrusting operators 8a to 8d of the first operating unit 9 and of the first to fourth operators 11a to 11d of the operating unit 12 will be substantially parallel to the setting surface S. Thus the operating device 1 can be set on the planar setting surface S and, with the palms set on the first and second grip portions 5, 6, the first to sixth operators 9, 12, 14, 15, 17 and 18 can be manipulated with free fingers.

The first operating unit 9 of the operating device 1 is explained in further detail. Referring to FIGS. 1, 9 and 10, the first operating unit 9 is designed so that the first to fourth thrusting operators 8a to 8d formed on a rotation actuating member 10 protrude into a substantially cross-shaped recess 30 towards one end of the upper surface of the main body portion 4. On upper, lower, left and right ends of the cross-shaped recess 30 are formed bearing indicators 31a, 31b, 31c and 31d on the inner sides of which are formed four apertures 32 at right angles to one another for allowing the first to fourth thrusting operators 8a to 8d protrude towards the upper side of the main body portion 4. At a mid portion surrounded by these apertures 32 is formed a center support boss 33 for supporting the center of the upper surface of the rotation actuating member 10. This center support boss 33 is formed as-one with the inner upper surface of the main body portion 4. Facing the rotation actuating member 10 is mounted an elastic member 35 having four movable contacts 34 thrust by the first to fourth thrusting operators 8a to 8d. At the center of the elastic member 35 is held a spherically-shaped fulcrum element 36, such as a stainless steel ball, for supporting the center of the bottom surface of the rotation actuating member 10. Facing the elastic member 35 is arranged a circuit board 38 having four fixed contacts 37 associated with movable contacts 34.

Referring to FIGS. 9 and 10, the rotation actuating member 10 constituting the first operating unit 9 includes a circular-shaped base portion 39, first to fourth thrusting operators 8a to 8d formed as one on an upper portion of the base portion 39, a spherically-shaped first recess 41, a spherically-shaped second recess 42 and a contact guide 43. The first recess 41 is formed on the bottom surface of the center portion of the base portion 39 for engaging with the spherical surface of the fulcrum element 36, while the second recess 42 is formed on the upper surface of the center portion of the base portion 39 for engaging with the center support boss 33. The contact guide 43 is protuberantly formed on the lower surface of the base portion 39 for thrusting the back side of the movable contacts 34 of the elastic member 35. Referring to FIG. 9, the four thrusting operators 8a to 8d, formed as-one with the rotation actuating member 10, are formed on the upper surface of the base portion 39 so as to have facing ends tapered and so as to be thicker from the center towards the outer sides, and protrude from the upper surface side of the main body portion 4 via the respective apertures 32.

The elastic member 35 is sandwiched between the circuit board 38 and the rotation actuating member 10 and includes four movable rubber contacts 34 in association with the first to fourth thrusting operators 8a to 8d.

The fulcrum element 36 is spherically-shaped and is arranged at a central portion of the rotation actuating member 10 in register with the center support boss 33 so as to be

engaged in the first recess 41 formed the center of the rotation actuating member 10.

When the rotation actuating member 10 is arranged in the main body portion 4, the first to fourth thrusting operators 8a to 8d are arranged radially with the center support boss 33 as a center and are gradually increased in height from the facing ends towards the opposite outer ends. Thus, when the fingertip end is set on the center portion of the recess 30 surrounded by the first to fourth thrusting operators 8a to 8d, the relative position of the latter can be easily discerned by the tactile feel at the fingertip end and by the step difference between the center portion and the first to fourth thrusting operators 8a to 8d. Moreover, if the fingertip end is shifted during the switch operation from the center portion towards the outer side of the recess 30, it can be easily discerned by the tactile feel at the fingertip which of the first to fourth thrusting operators 8a to 8d is being thrust.

In the above-described structure of the first operating unit 9, if none of the first to fourth thrusting operators 8a to 8d is thrust, the rotation actuating member 10 is raised via the contact guide 43, under the bias of the elastic member 35, with the center support boss 33 becoming engaged in the spherically-shaped second recess 42 of the rotation actuating member 10. Simultaneously, the peripheral portion of the circular-shaped base portion 39 is retained by the ends of the apertures 32, so that the rotation actuating member 10 is retained in an initial position in which the first to fourth thrusting operators 8a to 8d protrude beyond the upper surface of the main body portion 4.

If, with the first to fourth thrusting operators 8a to 8d in the initial position, the third thrusting operator 8c is thrust in the direction of arrows A or B in FIG. 12, the rotation actuating member 10 is rotated in a direction indicated by arrow R1 or towards the right in FIG. 12, as the first recess 41 is rotated on the spherical surface of the fulcrum element 36, with the elastic member 35 being thrust downwards by the third thrusting operator 8c. If the third thrusting operator 8c is thrust further, the rotation actuating member 10 is further rotated in the direction of arrow R1 with the fulcrum element 36 as the center of rotation, as shown in FIG. 13, for establishing electrical connection by the movable contact 34 being contacted with the underlying fixed contact 37.

If the thrusting on the third thrusting operator 8c is released, the first recess 41 is moved in a direction away from the fulcrum element 36, with which it has so far been in contact, under the bias of the elastic member 35. That is, the third thrusting operator 8c is rotated in the direction of arrow R2 in FIG. 13 for spacing the movable contact 34 away from the fixed contact 37. If the third thrusting operator 8c is rotated further in the direction indicated by arrow R2 in FIG. 13, until the center support boss 33 is engaged with the second recess 42, the rotation actuating member 10 is reset to the initial position shown in FIG. 11.

On the other hand, if the first thrusting operator 8a is thrust towards the front side of the main body portion 4 as indicated by arrow C in FIG. 10, the elastic member 35 is deformed under its own elasticity so that, as the first recess 41 is rotated on the spherical surface of the fulcrum element 36, the first thrusting operator 8a is moved in a direction indicated by arrow C in FIG. 10 for realizing a switching operation by the movable contact 34 contacting the underlying fixed contact 37.

The movable contact 34 and the underlying fixed contact 37 make up a switch device and the switch on/off operation takes place by the movable contact 34 being contacted with or displaced away from the underlying fixed contact 37 to

permit inputting of a command signal for, for example, moving the display character.

In the operation of the first to fourth thrusting operators **8a** to **8d** of the first operating unit **9**, since the fulcrum point is formed by relative engagement of the spherically-shaped fulcrum element **36** and the spherically-shaped first recess **41**, the contact between the spherically-shaped surfaces is exploited for varying the stroke of the rotation actuating member **10** for realizing the switching operation. Moreover, the thrusting operators **8a** to **8d** are arranged in a segmented manner on the main body portion **4**, the direction of thrusting the first to fourth thrusting operators **8a** to **8d** is not limited in a fixed direction but the smooth switching operation may be realized by actuation from any arbitrary direction to prevent vibrations of the rotation actuating member **10** or shifting or distortion of the center position for improving operating characteristics.

The second operating unit **12** of the operating device **1** will be explained in further detail. Referring to FIGS. **1** and **2**, the second operating unit **12** has a substantially cross-shaped recess **53** on the opposite side end on the upper surface of the main body portion **4** and apertures **52** are formed at upper, lower, left and right ends of the recess **53**. The first to fourth thrusting operators **11a** to **11d** making up the second operating unit **12** are arranged on the main body portion **4** so that the distal ends thereof protrude from the upper surface of the main body portion **4**. Within the inside of the main body portion **4** are arranged switch devices actuated by the first to fourth thrusting operators **11a** to **11d**. These switch devices are turned on or off by thrusting the first to fourth thrusting operators **11a** to **11d** for entering a command signal for setting the functions or executing the operations of the display character.

On the distal end faces of the first to fourth thrusting operators **11a** to **11d** are inscribed symbols indicating the functions of the thrusting operators **11a** to **11d**, such as  $\square$ , X,  $\circ$  or  $\Delta$ . In the present embodiment, the first thrusting operator **11a**, second thrusting operator **11b**, third thrusting operator **11c** and the fourth thrusting operator **11d** are affixed with the symbols  $\Delta$ ,  $\square$ , X and  $\circ$ , respectively. Specifically, the third thrusting operator **11c** and the fourth thrusting operator **11d**, disposed towards the second grip portion **6** for facilitating the manipulation by the thumb finger, are reserved for entering command signals, such as "YES" or "NO", frequently used in playing the game. The third thrusting operator **11c** and the fourth thrusting operator **11d** therefore are affixed with marks  $\circ$  and X corresponding to the commands "YES" and "NO", respectively. Thus, in the operating device **1** designed to have a large number of operating units, the third and fourth thrusting operators **11c** and **11d** are placed at such positions as to permit facilitated manipulation to improve operability of the smallest number of thrusting operators required in playing the game.

The first to fourth thrusting operators **11a** to **11d** may be designed to display the respective functions by colors. That is, these first to fourth thrusting operators **11a** to **11d** may be of different colors for displaying their functions.

The third and fourth operating units **14** and **15** will now be explained. Referring to FIG. **1**, these third and fourth operating units **14** and **15** are arranged on substantially cylindrically-shaped mounting portions **47**, **48** at corner portions of the connection of the proximal ends of the first and second grip portions **5**, **6** to the main body portion **4**.

Since the third and fourth operating units **14** and **15** are of the same structure, the third operating unit **14** only is explained.

The third operating unit **14** has a multi-directional input device as shown in FIG. **14**. This multi-directional input device has a box-shaped upper frame **50** and an arched first interlock member **51**, as shown in FIG. **14**. This interlock member **51** has its warped end **52** engaged by a rotational shaft **54** of a first variable resistor **53a** constituting a rotary detector secured to a lateral side **50a** of the upper frame **50**. The interlock member **51** has on its opposite warped end **52** a boss **55** loosely fitted in an opening **56** formed in a lateral side **50b** facing the lateral side **50a** of the frame **50** for rotatably supporting the first interlock member **51** on the upper frame **50**.

An operating shaft **57** is mounted at the center of the upper frame **50**. This operating shaft **57** has a saucer-shaped operating member **58** and a disk **59** at its mid portion. This disk **59** has an orifice **60** and a rotation member **16** is mounted on the upper end of the operating shaft **57**.

Within the upper frame **50** is arranged a second interlock member **62** extending at right angles to the operating shaft **57**. The second interlock member **62** has a center ball **63** from which are transversely extended a pair of arms **64a**, **64b**. An elongated slot **65** extends from the upper surface to the lower surface of the ball **63**. The operating shaft **57** and the disk **59** are inserted into the elongated slot **65**. After registration of the orifice **60** in the disk **59** relative to a lateral side opening **66** in the ball **63**, a pin **67** is inserted into the opening **66** and the orifice **60**. The operating shaft **57** is thus mounted on the second interlock member **62** for rotation in the elongated slot **65** with the pin **67** as the center of rotation.

The end of the arm **64a** of the second interlock member **62** is engaged with the rotary shaft **54** of the second variable resistor **53b** secured to a lateral side **50c** of the upper frame **50**, while the end of the opposite side arm **64b** is fitted in an elongated opening **70** formed in the lateral side **50d** of the upper frame **50** so as to protrude outwardly from the lateral side **50d** of the upper frame **50**. The operating shaft **57** is passed through the elongated slot **71** in the first interlock member **51** so as to protrude outwards via an opening **72** in the upper surface of the upper frame **50**.

The operating shaft **57** is supported on a restoration member **73** having on its upper surface a recess **74** in which is rotatably housed the saucer-shaped operating member **58**.

On the lower end side of the upper frame **50** is mounted a lower frame **75**. The upper surface of the lower frame **75** is formed with a supporting wall section **77** for vertically movably housing a flange **76** of the restoration member **73**. Between the bottom surface of the lower frame **75** and an outer peripheral edge **78** of the restoration member **73** is housed a spirally extending return spring **79**. The restoration member **73** is biased upwards by this return spring **79**. The end of the opposite side arm **64b** of the second interlock member **62** is pressed against the upper edge of the elongated opening **70** on the lateral surface **50d** of the upper frame **50**. The second interlock member **62** is rotatably mounted on the upper frame **50** in a direction perpendicular to the first interlock member **51** below the first interlock member **51**.

On the lateral side **50d** of the upper frame **50** is mounted a thrust type switch device **80** which has its state changed over by pressing a spring-biased thrusting operator **81** against the spring bias. The switch device **80** has a thrusting operator facing an end **82** of arm **64b** of the second interlock member **62**. This end **82** protrudes in the same direction as a mounting leg **83** mounted on the lower edge of the upper frame **50** and terminals **84** of first and second variable resistors **53a**, **53b**.

The operating states of the multi-directional inputting device are as follows:

If the user grips the rotation member 16 for rotating the operating shaft 57 in an arbitrary direction, the operating shaft 57 is rotated about the point of intersection of the second interlock member 62 and the pin 67 as the center of rotation. With rotation of the operating shaft 57, the first interlock member 51 and the second interlock member 62 are rotated and further the rotational shafts 54 of the first and second variable resistors 53a, 53b are rotated for adjusting the resistance values.

The automatic restoration operation of the operating shaft 57 is as follows:

In a neutral state in which the operating shaft 57 is not in operation, the operating shaft 57 is upstanding through opening 72 in the upper surface of the upper frame 50. The bottom surface of the operating member 58 compresses against the inner bottom surface of the restoration member 73 by the return spring 79. If the operating shaft 57 is tilted from this state in the clockwise direction, as shown in FIG. 16, the flange 85, having an arcuate portion with a progressively increasing radius of curvature towards an outer side of the operating member 58, thrusts the restoration member 73 so that the restoration member 73 is moved downwards along the supporting wall section 77 of the lower frame 75 against the force of the return spring 79. If the operating force on the operating shaft 57 is released, the operating shaft 57 is reset to the neutral state shown in FIG. 15, that is to an upstanding position, under the bias of the return spring 79.

The operation of the switch device 80 is explained by referring to FIGS. 17 and 18.

In the non-operating state, the operating shaft 57 is in the position shown in FIG. 17 in which the end of the arm 64b of the second interlock member 62 is spaced apart from the thrusting operator 81 of the switch device 80, with the end of the arm 64b being pressed against the upper edge of the elongated opening 70 in the lateral side 50d of the frame 50. If the operating shaft 57 is pressed downwards from this state, the end of the arm 64b of the second interlock member 62 is moved downwards along the elongated opening 70, against the force of the return spring 79, with the engagement point of the arm 64a with the rotary shaft 54 of the variable resistor 53b as a fulcrum, until the end of the arm 64b is retained by the lower edge of the elongated opening 70 operating as a stop. In the interim, the end of the arm 64b thrusts the thrusting operator 81 of the switch device 80 downwards for changing over the state of the switch device 80. If the thrusting on the operating shaft 57 ceases, the end of the arm 64b is reset to the state shown in FIG. 17, under the force of repulsion of the return spring 79, with the end of the arm 64b being reset to the state of FIG. 17 in which it is abutted against the upper edge of the elongated slot 70. Meanwhile, the switch device 80 is operated even if the operating shaft 57 is thrust downwards when the actuating shaft 57 has been rotated in an optional direction.

Thus, by rotating the rotation member 16 for actuating the first and second variable resistors 53a, 53b, the third and fourth operators 14, 15 can issue the command information of continuously moving the display character with an accelerated movement, rotating the display character as it is advanced or varying the line of sight of the display character.

The fifth and sixth operating units 17, 18 arranged on the front side of the main body portion 4 are now explained.

The fifth and sixth operators 17, 18 are designed so that the first and second thrusting operators 19a, 19b, 20a, 20b

arranged on both sides on the front side of the main body portion 4 protrude at the distal ends thereof from the front surface of the main body portion 4 through upper and lower pairs of apertures 91 arranged parallel to each other. Within the main body portion 4 are arranged switch devices in association with these thrusting operators 19a, 19b and 20a, 20b.

The operating device 1 of the present invention is provided with a vibration imparting mechanism 92 for imparting vibrations to the user so that the game will be played with a higher simulated reality feeling. This vibration imparting mechanism 92 is provided on the proximal end of the first grip portion 5 held by the left hand when the user grips the operating device 1. This vibration imparting mechanism 92 is made up of a driving motor 93 driven by a driving command signal supplied from the main body portion of the game machine and an offset member 95 mounted on a driving shaft 94 of the driving motor 93. The offset member 95 is formed by a metallic member of a large weight mass to constitute a semi-circular weight 95a offset with respect to a fitting hole 96 into which is fitted the driving shaft 94 and which operates as a center of rotation. The driving motor 93, having the offset member 95 mounted on the driving shaft 94, is mounted by fitting the motor housing 98 in a fitting recess 97 in the form of a rectangular tube on the inner side of the first grip portion 5.

With the vibration imparting mechanism 92 constructed as described above, the driving motor 93 is driven for rotating the offset member 95, so that the driving motor 93 undergoes vibrations. These vibrations are transmitted via a peripheral wall section 97a constituting the fitting recess 97 to the first grip portion 5 and thence transmitted to the hands and fingers gripping the grip portion 5.

The vibration imparting mechanism 92 may also be provided on the second grip portion 6.

The above-described operating device 1 for the game machine according to the present invention is connected to a main body portion 101 of the game machine, as shown in FIG. 21.

The operating device 1 is connected to the main body portion 101 of the game machine by a connection cord 102 extending from the mid portion on the front side of the main body portion 4. This connection cord 102 has an end connector 103 which connects the operating device 1 to the main body portion 101 of the game machine by connecting the connector 103 to a jack 104 provided on a lateral surface of the main body portion 101 of the game machine.

The main body portion 101 of the game machine is provided with plural jacks 104 for connection to plural operating devices 1.

The main body portion 101 of the game machine is provided with a disc driving unit 105 for reproducing an optical disc having recorded thereon game programs and a picture processing device for displaying the display character along with the background picture on a screen of a television receiver in accordance with the game program recorded on the optical disc. The main body portion 101 of the game machine is also provided with a reset switch 106 for resetting the game then going on, a power switch 107 and a lid opening button 109 for opening a lid 108 adapted for opening/closing a disc mounting portion of the disc driving unit.

The main body portion 101 of the game machine is connected to a television receiver as a display device for displaying the display character along with a background picture for the game.

13

With the above-described operating device 1 for the game machine according to the present invention, the user can operate the first to sixth operating units 9, 12, 14, 15, 17 or 18, using ten fingers at the maximum, as the first and second grip portions 5, 6 are held with both hands. The operating device for the game machine can also be operated with only one of the first and second grip portions 5, 6 gripped. That is, by properly actuating the first to sixth operating units 9, 12, 14, 15, 17 or 18, not only can the display character be moved horizontally, but also the display character can be rotated or moved with accelerated movements in meeting with the game with the three-dimensional spatial picture. Moreover, since vibrations can be imparted to the user, the game can be played with excellent simulated reality feeling.

Thus, by using the operating device 1 for the game machine according to the present invention, the display character can perform complex movements to carry out a game program with improved simulated reality feeling. For example, such a game can be played in which an airplane or a submarine is moved through a three-dimensional spacing.

With the operating device for a game machine according to the present invention, the third and fourth operating units provided with signal input elements manipulated by rotation members are provided facing each other on the proximal ends of the first and second grip portions, so that a game program can be easily executed which has a display character capable of executing variegated movements. In addition, a vibration imparting mechanism is provided in the operating device for the game machine so that vibrations can be imparted to the user during the game for enabling the game to be played with improved simulated reality feeling.

What is claimed is:

1. An operating device for a game machine, comprising:
  - a main body having front and rear sides and upper and lower surfaces;
  - first and second grips protruding at spaced positions from end parts;
  - a first operating unit mounted in said main body adjacent one of said spaced positions, said first operating unit having a plurality of first thrusting operators protruding from said upper surface of said main body and a plurality of signal input elements each for generating a signal when a corresponding one of said first thrusting operators is depressed;
  - a second operating unit mounted in said main body adjacent the other one of said spaced positions, said second operating unit having a plurality of second thrusting operators protruding from said upper surface of said main body and a plurality of signal input elements each for generating a signal when a corresponding one of said second thrusting operators is depressed; and
  - third and fourth operating units arranged on said rear side of said main body, said third operating unit being positioned adjacent said first grip and said fourth operating unit being positioned adjacent said second grip so that said third and fourth operating units confront one another, said third and fourth operating units each having a rotation member and at least one signal input element for generating a signal in response to an operation of said rotation member.
2. The operating device as claimed in claim 1, wherein said first and second grips protrude from said main body so as to be directed downwardly from said main body.

14

3. The operating device as claimed in claim 1, wherein said first thrusting operators are interconnected at right angles to one another at a midpoint and are arranged for pivoting movement about said midpoint.

4. The operating device as claimed in claim 1, further comprising engagement recesses formed on said lower surface of said main body, said engagement recesses adapted to be engaged by part of a user's hand or finger when said first and second grips are gripped by the user's hand or finger.

5. The operating device as claimed in claim 4, further comprising finger supports protruding from said lower surface of said main body in register with said engagement recesses.

6. The operating device as claimed in claim 1, further comprising fifth and sixth operating units arranged on said front side of said main body.

7. The operating device as claimed in claim 1, further comprising a switching unit for switching the operating modes of said third and fourth operating units.

8. The operating device as claimed in claim 1, further comprising a vibration imparting mechanism.

9. The operating device as claimed in claim 8, wherein said vibration imparting mechanism is arranged in at least one of said first and second grips.

10. The operating device as claimed in claim 8, wherein said vibration imparting mechanism includes a driving motor having a driving shaft and an eccentric member mounted on said driving shaft.

11. A game machines, comprising  
 a main unit for reading a game program; and  
 an operating device interconnected with said main unit, said operating device including  
 a main body having front and rear sides and upper and lower surfaces;  
 first and second grips protruding at spaced positions from said rear side of said main body ;  
 a first operating unit mounted in said main body adjacent one of said spaced positions, said first operating unit having a plurality of first thrusting operators protruding from said upper surface of said main body and a plurality of signal input elements each for generating a signal when a corresponding one of said first thrusting operators is depressed;  
 a second operating unit mounted in said main body adjacent the other one of said spaced positions, said second operating unit having a plurality of second thrusting operators protruding from said upper surface of said main body and a plurality of signal input elements each for generating a signal when a corresponding one of said second thrusting operators is depressed; and  
 third and fourth operating units arranged on said rear side of said main body, said third operating unit being positioned adjacent said first grip and said fourth operating unit being positioned adjacent said second grip so that said third and fourth operating units confront one another, said third and fourth operating units each having a rotation member and at least one signal input element for generating a signal in response to an operation of said rotation member.

12. The game machine as claimed in claim 11, wherein said first and second grips protrude from said main body so as to be directed downwardly from said main body.

**15**

13. The game machine as claimed in claim 11, wherein said first thrusting operators are interconnected at right angles to one another at a midpoint and are arranged for pivoting movement about said midpoint.

14. The game machine as claimed in claim 11, further comprising engagement recesses formed on said lower surface of said main body, said engagement recesses adapted to be engaged by part of a user's hand and finger when said first and second grips are gripped by the user's hand or finger.

15. The game machine as claimed in claim 14, further comprising finger supports protruding from said lower surface of said main body in register with said engagement recesses.

16. The game machine as claimed in claim 11, further comprising fifth and sixth operating units arranged on end sides on the front said front surface of said main body.

**16**

17. The game machine as claimed in claim 11, further comprising a switching unit for switching the operating modes of said third and fourth operating units.

18. The game machine as claimed in claim 11, further comprising a vibration imparting mechanism.

19. The game machine as claimed in claim 18, wherein said vibration imparting mechanism is arranged in at least one of said first and second grips.

20. The game machine as claimed in claim 18, wherein said vibration imparting mechanism includes a driving motor having a drive shaft and an eccentric member mounted on said driving shaft .

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,231,444 B1  
DATED : May 15, 2001  
INVENTOR(S) : Goto et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 5,

Line 13, after "11d" insert a period.

Column 6,

Line 41, after the word "and" delete the word "the".

Column 7,

Lines 29 and 55, "as-one" should read -- as one --.

Column 8,

Line 13, after the word "fingertip" delete the word "end".

Column 11,

Line 15, "thought" should read -- through --.

Column 13,

Line 39, "end parts" should read -- said rear side of said main body --.

Column 14,

Line 31, "machines" should read -- machine --.

Column 15,

Lines 15 & 16, after the word "on" delete the words "end sides on the front".

Signed and Sealed this

Second Day of April, 2002

Attest:



Attesting Officer

JAMES E. ROGAN  
Director of the United States Patent and Trademark Office